

The world's fastest tripod.

Multi-award winning **flowtech**® is incredibly fast, lightweight and easy to set up and adjust compared to any other tripod. Giving you ultimate versatility with an improved workflow.

Performance tested in extreme conditions, **flowtech**® is a revolution in tripod technology. Try it and join the revolution.

- ▷ **Deploy and adjust your tripod in an instant:** Unique quick release brakes
- ▷ **Easy to transport and exceptional torsional stiffness:** Ergonomic carbon fibre leg design
- ▷ **Capture extremely low and high shots:** Versatile hinge lock mechanism
- ▷ **Superior performance and reliability:** Extensive endurance and environmental testing



75mm 100mm



sachtler 

SKU	flowtech75 aktiv MS 4585	flowtech75 aktiv GS 4587	flowtech100 MS 5585	flowtech100 GS 5587	flowtech100 5584
Payload	20 kg / 44 lb	20 kg / 44 lb	30 kg / 66 lb	30 kg / 66 lb	30 kg / 66 lb
Spreader material	Lightweight	With foot operation and detachable rubber feet	Carbon fibre, adjustable angles	With foot operation and detachable rubber feet	No spreader included
Weight (Tripod only)	2.9 kg / 6.4 lb	2.9 kg / 6.4 lb	3.2 kg / 7.1 lb	3.2 kg / 7.1 lb	3.2kg / 7.1lb
Weight (Tripod with rubber feet and spreader)	3.5 kg / 7.7 lb	3.8 kg / 8.4 lb	4.1 kg / 9.1 lb	4 kg / 8.8 lb	3.4 kg / 7.4 lb
Without spreader mode height range	26 - 153 cm 10.2 - 60.2 in	26 - 153 cm 10.2 - 60.2 in	26 - 153cm 10.2 - 60.2 in	26 - 153 cm 10.2 - 60.2 in	26 - 153 cm 10.2 - 60.2 in
Spreader height range	63 - 157 cm 24.8 - 61.8 in	41 - 158 cm 16.1 - 62.2 in	52 - 155 cm 20.5 - 61in	43 - 159 cm 16.9 - 62.6in	No spreader included



**Mid-level
spreader
Systems**



Ace XL flowtech75 1017MS	aktiv6 flowtech75 MS S2064S-FTMS	aktiv8 flowtech75 MS S2068S-FTMS	aktiv8T flowtech75 MS S2068T-FTMS	SKU	aktiv10 flowtech100 S2072S-FT	aktiv10 flowtech100 MS S2072S-FTMS	aktiv10T flowtech10T MS S2072T-FTMS	aktiv12T flowtech10T MS S2074T-FTMS	aktiv14T flowtech10T MS S2076T-FTMS	Video 18 flowtech100 MS 1811FTMS	Cine 7+7 flowtech100 MS 1910FTMS
2 - 8 kg 4.4 - 17.6 lb	0 - 8 kg 0 - 17.6 lb	0 - 12 kg 0 - 26.5 lb	0 - 12 kg 0 - 26.5 lb	Payload range	0 - 12 kg 0 - 26.5 lb	0 - 12 kg 0 - 26.5 lb	0 - 12 kg 0 - 26.5 lb	0 - 14kg 0 - 30.9 lb	0 - 16 kg 0 - 35.3 lb	2 - 22kg 4 - 48lb	2 - 22kg 4 - 48lb
8 steps	15+0	15+0	15+0	Counterbalance	15+0	15+0	15+0	15+0	15+0	16 steps + boost button	16 steps + boost button
3 / 3 + 0	3 / 3 + 0	7 / 7 + 0	7 / 7 + 0	Drag	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0
104 mm 4.1 in	120 mm 4.7 in	120 mm 4.7 in	60 mm 2.4 in	Balance range	120 mm 4.7 in	120 mm 4.7 in	60 mm 2.4 in	70 mm 2.8 in	70 mm 2.8 in	120 mm 4.7 in	150 mm 5.9 in
Ace Plate	Sideload S	Sideload S	Touch & Go S	Camera fitting	Sideload S	Sideload S	Touch & Go S	Touch & Go 16	Touch & Go 16	Touch & Go 16	Sideload M
5.3 kg / 11.7 lb	6.2 kg / 13.7 lb	6.3 kg / 13.9 lb	6.4 kg / 14.1 lb	Weight	6.3 kg / 13.9 lb	6.9 kg / 15.2 lb	7 kg / 15.3 lb	7.4 kg / 16.3 lb	7.5 kg / 16.5 lb	8.2 kg / 18.1 lb	8.3 kg / 18.3 lb
41 - 169 cm 16.1 - 66.5 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	Height range without spreader	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	42 - 172 cm 16.5 - 67.7 in	41 - 170 cm 16.1 - 66.9 in
78 - 173 cm 30.7 - 68.1 in	79 - 174 cm 31.1 - 68.5 in	79 - 174 cm 31.1 - 68.5 in	79 - 174 cm 31.1 - 68.5 in	Height range with mid-level spreader	-	71 - 172 cm 27.9 - 67.7 in	71 - 172 cm 27.9 - 67.6 in	71 - 172 cm 27.9 - 67.7 in	72 - 172 cm 27.9 - 67.7 in	72 - 173 cm 28.3 - 68.1 in	71 - 172 cm 28 - 67.7 in



**Ground
spreader
Systems**



Ace XL flowtech75 GS 1017GS	aktiv6 flowtech75 GS S2064S-FTGS	aktiv8 flowtech75 GS S2068S-FTGS	aktiv8T flowtech75 GS S2068T-FTGS	SKU	aktiv10 flowtech100 GS S2072S-FTGS	aktiv10T flowtech100 GS S2072T-FTGS	aktiv12T flowtech100 GS S2074T-FTGS	aktiv14T flowtech100 GS S2076T-FTGS	Video 18 flowtech100 GS 1811FTGS	Cine 7+7 flowtech100GS 1910FTGS
2 - 8 kg 4.4 - 17.6 lb	0 - 8 kg 0 - 17.6 lb	0 - 12 kg 0 - 26.5 lb	0 - 12 kg 0 - 26.5 lb	Payload range	0 - 12 kg 0 - 26.5 lb	0 - 12 kg 0 - 26.5 lb	0 - 14 kg 0 - 30.9 lb	0 - 16 kg 0 - 35.3 lb	2 - 22kg 4 - 48lb	2 - 22kg 4 - 48lb
8 steps	15+0	15+0	15+0	Counterbalance	15+0	15+0	15+0	15+0	16 steps + boost button	16 steps + boost button
3 / 3 + 0	3 / 3 + 0	7 / 7 + 0	7 / 7 + 0	Drag	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0
104 mm 4.1 in	120 mm 4.7 in	120 mm 4.7 in	60 mm 2.4 in	Balance range	120 mm 4.7 in	60 mm 2.4 in	70 mm 2.8 in	70 mm 2.8 in	120 mm 4.7 in	150 mm 5.9 in
Ace Plate	Sideload S	Sideload S	Touch & Go S	Camera fitting	Sideload S	Touch & Go S	Touch & Go 16	Touch & Go 16	Touch & Go 16	Sideload M
5.5k g / 12.1 lb	6.4 kg / 14.1 lb	6.5 kg / 14.3 lb	6.6 kg / 14.5 lb	Weight	6.8 kg / 15 lb	7.0 kg / 15.3 lb	7.3 kg / 16.1 lb	7.4 kg / 16.3 lb	8.2 kg / 18.1 lb	8.2 kg / 18.1 lb
41 - 169 cm 16.1 - 66.5 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	Height range without spreader	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	23 - 170 cm 9.0 - 66.9 in	42 - 172 cm 16.5 - 67.7 in	41 - 170 cm 16.1 - 66.9 in
57 - 174 cm 22.4 - 68.5 in	56 - 176 cm 22 - 69.3 in	56 - 176 cm 22 - 69.3 in	56 - 176 cm 22 - 69.3 in	Height range with ground spreader	60 - 176 cm 23.6 - 69.3 in	60 - 176 cm 23.6 - 69.3 in	60 - 176 cm 23.6 - 69.3 in	60 - 176 cm 23.6 - 69.3 in	61 - 177 cm 24 - 69.7 in	60 - 176 cm 23.6 - 69.3 in