



# FSB 14T *Mk II*



## Fluid, Smooth, Balanced

### Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.

- **Smooth operation.**  
Create precision pans with smooth starts and soft stops.
- **Finely balanced.**  
Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg.
- **Always on the level.**  
Innovative illuminated PrismBubble visible from any height – day or night.
- **Built for endurance**  
Engineered to the highest standards with tough materials and precision components.



### **FSB 14T Mk II** S2077-0001

**Bowl size:** 100mm with integrated flat base  
**Payload Range:** 0 -16 kg / 0 - 35.3 lb  
**Counterbalance steps:** 15+0  
**Drag setting:** 7+0  
**Camera fitting:** Touch & Go 16  
**Weight:** 3.2 / 7.1 lb

**Level:** Illuminated PrismBubble  
**Sliding range:** 70 mm / 2.8 in  
**Tilt range:** +90° to -70°  
**Temperature range:**  
-40°C to +60°C / -40°F to +140°F

# 14



# Fluid, Smooth, Balanced

## 1 Smooth operation.

Create precision pans with smooth starts and soft stops. The drag system delivers consistently smooth camera movements, fine-tuned to your payload.

## 2 Finely balanced.

Steady shots are standard with FSB. Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg, the widest range of cameras can be finely balanced in the perfect position.

## 3 Always on the level.

Instant confirmation that the camera is level comes from the innovative illuminated PrismBubble visible from any height – day or night.

## 4 Built for endurance.

Engineered to the highest standards with tough materials and precision components, FSB is built for endurance. With no variation in performance in the widest range of temperatures and environments, FSB is the first choice for outdoor operators.



## FSB 14T Mk II



**System FSB 14T Mk II  
ENG CF GS**  
1442M



**System FSB 14T Mk II  
ENG CF MS**  
1443M



**System FSB 14T Mk II  
HotPod**  
1446M



**System FSB 14T Mk II  
Ped C III**  
1470M

Spreader type	Ground spreader	Mid-level spreader	Mid-level spreader	
<b>Bowl</b>	100 mm	100 mm	100 mm	100 mm
<b>Payload range</b>	0 - 16 kg / 0 - 35.3 lb	0 - 16 kg / 0 - 35.3 lb	0 - 16 kg / 0 - 35.3 lb	0 - 16 kg / 0 - 35.3 lb
<b>Counterbalance steps</b>	15+0	15+0	15+0	15+0
<b>Drag setting</b>	7+0	7+0	7+0	7+0
<b>Balance range</b>	70 mm / 2.8 in	70 mm / 2.8 in	70 mm / 2.8 in	70 mm / 2.8 in
<b>Tilt range</b>	+90° to -70°	+90° to -70°	+90° to -70°	+90° to -70°
<b>Camera fitting</b>	Touch & Go 16	Touch & Go 16	Touch & Go 16	Touch & Go 16
<b>System weight</b>	6.6 kg / 14.6 lb	7.1 kg / 15.7 lb	8.5 kg / 18.7 lb	19.9 kg / 43.9 lb
<b>Height range</b>	62 - 170 cm / 24.4 - 66.9 in	66 - 168 cm / 26 - 66.1 in	95 - 190 cm / 37.4 - 74.8 in	91 - 175 cm / 35.8 - 68.9 in
<b>Transport length</b>	89 cm / 35 in	89 cm / 35 in	101 cm / 39.8 in	
<b>Tripod stages</b>	2	2	1	
<b>Tripod material</b>	Carbon fibre	Carbon fibre	Carbon fibre	Aluminium