



System Cine 30 EFP CF MS

SKU: 3013

- Versatile Sachtler Cine System
- Supports camera setups from 3 – 32kg (7 - 71 lb)
- SpeedBalance: 18 steps with boost button
- 7 steps of pan and tilt drag
- Sideload platform
- Lightweight 2-stage heavy-duty carbon fibre tripod
- Mid-level spreader, and front pan bar included



PRODUCT DESCRIPTION

The Sachtler Cine 30 is the reliable and flexible solution for daily Cine use. Its Sideload platform allows for simple and secure mounting of heavily accessorised camera setups, ensuring safety without compromising efficiency. With a payload range that spans from 3 kg to 32 kg (7 to 71 lb), the Cine 30 offers optimal versatility for diverse shooting scenarios.

SpeedBalance technology with 18 counterbalance steps ensures your camera is quickly balanced and consistently supported at any angle. The frictionless fluid drag with seven levels of drag guarantees smooth and seamless pans, and a front pan bar helps to deliver extra control.

In this system the versatile Cine 30 is combined with a 2-stage carbon fibre tripod. The Sachtler EFP 2 CF Heavy-Duty Carbon Fibre Tripod helps crews all over the world create amazing results in a range of environments. The lightweight carbon fibre design is stable and twist resistant, while the quick clamps make it simple to setup and start. Making everything easier is a built-in transport safety cord that prevents the legs from opening while you are moving the tripod.

Crafted with precision engineering and robust materials, the System Cine 30 EFP CF MS is built to withstand the rigours of Cine production. Take your daily set life to the next level with a fluid head system that seamlessly combines reliability and adaptability.


TECHNICAL SPECIFICATIONS

Range	Cine
Bowl Size	150 mm
Interface Compatibility	Sideload
Spreader Type	Mid-level spreader
Material	Carbon Fibre
Payload	3 kg to 32 kg 6.6 lb to 70.5 lb
Counterbalance	18 counterbalance steps + Boost Button
Drag	7 + 0 drag settings
Weight	12.2 kg 26.9 lb
Tripod Stages	2
Pan Bar Count	1
Sliding Range	15 cm 5.9 in
Tilt Range	90° to -75°
Temperature Range	-40 °C to 60 °C -40 °F to 140 °F
Transport Length	95 cm 37.4 in
Level Bubble	Yes, illuminated
Adaptor Viewfinder Extension	Included Adaptor
Height	77 cm to 173 cm 30.3 in to 68.1 in


IN THE BOX


- [3007 - Cine 30](#)
- [3372 - Front pan bar HD](#)
- [6386 - Tripod EFP 2 CF](#)
- [7007 - Mid-level spreader 100/150](#)
- [7004 - Rubber Feet 100/150](#)

DIAGRAMS



Half ball with integrated flat base





YOU MAY ALSO LIKE...



[System Cine 30](#)



[System Cine 30 EFP CF GS](#)