



# Electro Storm CS15 Feature Sheet

## Main Features

- **1585W Full-Color Point-Source LED with Ultra-High Color Quality**
- **Daylight Output Comparable to 1800W HMI** Such As Arri M18
- **Dual Accessory Mount** (Aputure Mount & Bowens Mount)
- **Electronic Aputure Mount** Compatible with Aputure Mount Reflectors (20°, 35°, 50°), F14 Fresnel, and other Large or Powered Accessories<sup>1</sup>
- **Auto Output Calibration & Optimization** using Aputure Mount Modifiers
- **Upgraded High SSI LEDs: SSI (D56): 86+, SSI (Tungsten): 89+ – Significantly Improved Spectral Continuity and Light Quality**
- **IP65 Dust & Water-Resistant**
- Redesigned Heatsink with **Advanced Liquid-Cooling Technology**
- **High-Output Control Box** with Side & Top-Facing Ports
- **Included Control Box Handcart** for Easy Transportation
- **Removable Heavy-Duty Yoke** – Remove for Better Ergonomics or Use with Motorized Yoke
- Optional **Motorized Yoke** For Smooth Remote Operation of **Pan/Tilt**
- **PWM & High-Speed Flicker-Free** Dimming Modes
- **>90% of Colors Within Rec.2020 Color Space**
- **Fully Tunable CCT** from 2,000K to 10,000K
- Fully-Tunable **Green-Magenta Adjustment** (Full Plus/Minus Green)
- **0.1-100% Stepless** Brightness Control – with Improved Low-End Dimming
- **Advanced HSI** with White Point CCT Control
- **Industry-standard xy** (CIE 1931), RGB, Light Source, & 300+ Gel Presets
- **Multiple Control Methods:** Sidus Link App Control, LumenRadio CRMX, Art-net & sACN via etherCON, 16-bit 5-Pin DMX512 In & Out
- **15 Built-in Lighting FX**
- **2 Output Modes:** Max & Constant
- **Supports Battery Operation** via Dual 48V DC Inputs

<sup>1</sup>Additional Aputure Mount Accessories and Modifiers will be available in the future.

## Product Description

The Electro Storm CS15 is a 1585W high-output full-color point-source LED fixture with ultra-high color quality for professionals – featuring dual accessory mounts, professional connectivity methods, high SSI color quality, and an IP65 dust & water-resistant construction. At 1585W of intense power output, the Electro Storm CS15 is bright enough to be comparable to industry-standard 1800W HMIs and is the most powerful and color-accurate open-face full-color point-source fixture on the market to date.

With dual accessory mounts, the Electro Storm CS15 features both the universal Bowens Mount and all-new electronic Aputure Mount compatibility, making it one of the most adaptable fixtures on the market. Designed with higher stability, durability, and optimization for heavy-duty modifiers, the Aputure Mount is compatible with 3 new reflectors (20°, 35°, & 50°) and the 14-inch F14 Fresnel, and communicates data for both optimized color accuracy and motorized focus control.

Expanding the motorized electronic accessories designed for the Electro Storm CS15, it is also compatible with an optional Motorized Yoke for smooth remote operation of pan and tilt adjustments when suspended or rigged in hard-to-reach areas, drastically increasing workflow efficiency on set.

In addition to its intense power output, the full-color LED chipset is capable of expanded color controls across its wide 2,000K to 10,000K CCT range with green-magenta adjustment and >90% coverage of colors within the Rec. 2020 color space. By utilizing a new dual-blue LED chipset design, the Electro Storm CS15 also achieves stunning spectral reproduction with an ultra-high SSI (Tungsten) of 89+ and SSI (D56) of 86+, ensuring industry-leading color quality across all shooting environments.

To cool this fixture's massive LED engine, the Electro Storm CS15 is equipped with advanced liquid-cooling technology to give users access to as much light as possible.

Designed for professionals, the Electro Storm CS15 features advanced connectivity options (including Sidus Link app control, LumenRadio CRMX, Art-net & sACN via etherCON, and 16-bit DMX512). And with its rugged IP65 dust and weather-resistant construction, the Electro Storm CS15 can withstand the most demanding filming environments without worrying about performance or reliability.

## Sales & Shipping Information

|                    |  |
|--------------------|--|
| Product Name       | Electro Storm CS15                           |
|                    | <b>Product code</b>                          |
| UK Plug            | 6971842188499                                |
| EU Plug            | 6971842188475                                |
| Without AC Plug    | 6971842188529                                |
| Packing Dimensions | 98.0 x 84.0 x 68.0cm<br>38.6 x 33.1 x 26.8in |
| Net Weight         | 59.0kg / 130.1lbs                            |
| Gross Weight       | 88.5kg / 195.1lbs                            |
| Carton Quantity    | 1 pcs  |
| Carton Dimensions  | TBD  |
| Carton Weight      | TBD  |

## Target Audience

The Electro Storm CS15 is ideal for professional filmmakers and lighting technicians who need the most versatile and brightest modifiable full-color point-source on the market to illuminate large areas with a high-output full-color light and industry-leading color quality.

Professionals working on set will appreciate the optimization and versatility of the Electro Storm CS15's dual Bowens and all-new electronic Aputure Mount accessory system. This system provides owner-operators and lighting technicians with a plethora of options, from using existing Bowens Mount modifiers, to the new Spotlight Max projection lens or Aputure Mount F14 Fresnel – creating combinations for any environment.

As a professional fixture, the Electro Storm CS15 can seamlessly sync into existing lighting workflows with its LumenRadio CRMX, Art-net & sACN via etherCON, and 16-bit DMX512 controls. And with Sidus Link app control and the optional motorized yoke, the Electro Storm CS15 can be adjusted remotely when in hard-to-reach places.

From virtual production studios to rugged professional film sets, the IP65-rated Electro Storm CS15 is an industry-leading full-color point-source LED that belongs in any professional's lighting kit.



## Electro Storm CS15 Photometrics

| CCT     | Dis. | No Reflector        | 50° Reflector          | 35° Reflector          | 20° Reflector          |
|---------|------|---------------------|------------------------|------------------------|------------------------|
| 2,000K  | 3m   | 1,818 lux<br>169 fc | 5,310 lux<br>493 fc    | 10,340 lux<br>961 fc   | 30,100 lux<br>2,796 fc |
|         | 5m   | 712 lux<br>66 fc    | 2,034 lux<br>189 fc    | 3,710 lux<br>345 fc    | 10,450 lux<br>971 fc   |
| 3,200K  | 3m   | 5,040 lux<br>468 fc | 15,210 lux<br>1,413 fc | 28,880 lux<br>2,683 fc | 85,400 lux<br>7,934 fc |
|         | 5m   | 1,827 lux<br>170 fc | 5,760 lux<br>535 fc    | 10,610 lux<br>986 fc   | 30,100 lux<br>2,796 fc |
| 4,300K  | 3m   | 5,210 lux<br>484 fc | 15,980 lux<br>1,485 fc | 31,110 lux<br>2,889 fc | 91,800 lux<br>8,528 fc |
|         | 5m   | 2,056 lux<br>191 fc | 6,120 lux<br>569 fc    | 11,080 lux<br>1,029 fc | 31,600 lux<br>2,936 fc |
| 5,600K  | 3m   | 5,540 lux<br>515 fc | 16,740 lux<br>1,555 fc | 32,600 lux<br>3,029 fc | 94,500 lux<br>8,779 fc |
|         | 5m   | 2,143 lux<br>199 fc | 6,420 lux<br>596 fc    | 11,650 lux<br>1,082 fc | 33,100 lux<br>3,075 fc |
| 10,000K | 3m   | 4,870 lux<br>452 fc | 14,420 lux<br>1,340 fc | 27,500 lux<br>2,555 fc | 82,400 lux<br>7,655 fc |
|         | 5m   | 1,911 lux<br>178 fc | 5,530 lux<br>514 fc    | 10,050 lux<br>934 fc   | 28,600 lux<br>2,657 fc |
| Red     | 3m   | TBD                 | TBD                    | TBD                    | TBD                    |
|         | 5m   | TBD                 | TBD                    | TBD                    | TBD                    |
| Green   | 3m   | TBD                 | TBD                    | TBD                    | TBD                    |
|         | 5m   | TBD                 | TBD                    | TBD                    | TBD                    |
| Blue    | 3m   | TBD                 | TBD                    | TBD                    | TBD                    |
|         | 5m   | TBD                 | TBD                    | TBD                    | TBD                    |



## What's in the Box

| Name  | Qty |
|---|-----|
| Electro Storm CS15                                      | 1   |
| Removable Yoke for Electro Storm CS15                   | 1   |
| Electro Storm CS15 Pro Control Box                      | 1   |
| Electro Storm CS15 Control Box Handcart                 | 1   |
| Electro Storm CS15 Head Cable (15m)                     | 1   |
| AC Power Cable for Electro Storm CS15 (6m)              | 1   |
| Aputure Mount 35° Reflector (Electro Storm CS15 / XT26) | 1   |
| Barn Doors for Aputure Mount Reflectors (35° / 50°)     | 1   |
| Barn Doors Adapter                                      | 1   |
| Aputure Mount Protection Cover                          | 1   |

## Electro Storm CS15 Specifications

|                                     |  |   |
|-------------------------------------|--|---|
| CCT                                 | 2000K – 10,000K  |   |
| CRI                                 | 98   |   |
| TLCI                                | 98   |   |
| CQS                                 | 97   |   |
| SSI (Tungsten)                      | 90   |   |
| SSI (D56)                           | 86   |   |
| TM-30 RF (Average)                  | 93   |   |
| TM-30 RG (Average)                  | 101  |   |
| Max Power Consumption               | 2200W  |   |
| Max Power Output                    | 1585W  |   |
| Weather Resistance Rating           | IP65   |   |
| Beam Angle (No Reflector)           | 62°  |   |
| Compatible Aputure Mount Reflectors | 20° / 35° / 50°  |   |
| Operating Voltage                   | DC1 & DC2  | 48V / 19A   |
|                                     | AC   | 100V ~ 240V / 23A-9A / 50-60 Hz                   |
| Operating Temperature               | -20°C ~ 45°C / -4°F ~ 113°F                                  |   |
| Storage Temperature                 | -40°C ~ 85°C / -40°F ~ 185°F                                 |   |
| Control Methods                     | On-board, Sidus Link App, DMX/RDM, CRMX, etherCON            |   |
| Firmware Upgradeable                | Sidus Link, USB Drive  |   |
| Wireless Range (Bluetooth & CRMX)   | ≤100m / ≤328.1ft   |   |
| Screen Type                         | TFT  |   |
| Cooling Method                      | Liquid Cooling   |   |
| Fan Noise Levels                    | High Speed Mode  | 44dB  |
|                                     | Default Mode   | 39dB  |
|                                     | Silent Mode  | 30dB  |
| Weight                              | Lamp Head w/o Yoke   | 18kg / 39.7lbs                                    |
|                                     | Removable Yoke for Electro Storm CS15                        | 3.2kg / 7.1lbs                                    |
|                                     | Control Box  | 19kg / 41.9lbs                                    |
|                                     | Aputure Mount 20° Reflector                                  | 3.8kg / 8.4lbs                                    |
|                                     | Aputure Mount 35° Reflector                                  | 1.5kg / 3.3lbs                                    |
|                                     | Aputure Mount 50° Reflector                                  | 1.2kg / 2.7lbs                                    |
|                                     | Barn Doors for Aputure Mount Reflectors (35° / 50°)          | 1.5kg / 3.3lbs                                    |
| Dimensions                          | Lamp Head w/o Yoke   | 45.7 x 35.2 x 28.1cm<br>17.99 x 13.86 x 11.06in   |
|                                     | Removable Yoke for Electro Storm CS15                        | 59.1 x 8.8 x 49.7cm<br>23.27 x 3.46 x 19.57in     |
|                                     | Control Box  | 27.3 x 26.2 x 55.0cm<br>10.75 x 10.31 x 21.65in   |
|                                     | Aputure Mount 20° Reflector                                  | 53.73 x 41.06 x 37.4cm<br>21.15 x 16.17 x 14.72in |
|                                     | Aputure Mount 35° Reflector                                  | 27.7 x 26.6 x 25.0cm<br>10.91 x 10.47 x 9.84in    |
|                                     | Aputure Mount 50° Reflector                                  | 27.7 x 19.18 x 25.0cm<br>10.91 x 7.55 x 9.84in    |
|                                     | Barn Doors for Aputure Mount Reflectors (35° / 50°) [Closed] | 28.23 x 30.2 x 4.0cm<br>11.11 x 11.89 x 1.57in    |