


- TALUS fixed downlight is available for surface and pendant installation.
- 3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux

Model (LED Power*)	CCT**	CRI80, CRI90 LED Source	Type	Beam Angle	Colour	Dimming Option***	Accessories
		80 (80) 90 (90)					
TALUS Surface 23.9W <i>(TALUS SF 24)</i>	2700K (27B) 3000K (30B) 4000K (40B)	3621lm 3847lm 3304lm	Fixed (FX)	20° (20) 40° (40) 60° (60)	White (WH) Black (BL)	Without Driver (00) Non Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Push Button (PB) Phase Cut (PC)	ANTI-GLARE SHIELD White Matt (1X) Black Matt (2X) Gold Matt (3X)  EXTRAS No Extras (0)
TALUS Pendant 23.9W <i>(TALUS PD 24)</i>	5700K (57B)	3847lm		-			
TALUS Surface 31.3W <i>(TALUS SF 31)</i>	2700K (27B) 3000K (30B) 4000K (40B)	4510lm 4792lm 4115lm		Fixed (FX)	20° (20) 40° (40) 60° (60)	White (WH) Black (BL)	
TALUS Pendant 31.3W <i>(TALUS PD 31)</i>	5700K (57B)	4792lm	-				
Warm Dimmable							
TALUS WD Surface 30.7W <i>(TALUS WD SF 31)</i>	Warm Dimmable 1800K–3000K (WD)	CRI95 LED Source 95 (95) 2840lm					
TALUS WD Pendant 30.7W <i>(TALUS WD PD 31)</i>							

* In 31W models the driver must be externally installed.

** Models with CCTs of 3500K, 5000K & 6500K are available upon request.

*** DMX drivers for Pendant (24W & 31W) and 31W Surface models must be externally installed.

Ordering Code Example: TALUS SF31-30B-80-FX-60-BL-DL-20

